




APPLICATION:		PRODUCT NAME: PRE-RINSE, SPRING STYLE, BACKSPASH MOUNT	
JOB NAME:		SPECIAL CONFIGURATION ■ 64793 CHECK BASE MODEL AND OPTIONS	
QUANTITY:	ITEM NO.	MODEL: ■ 13390 ULTRA SPRAY VALVE, WALL BRACKET □ 13366 ULTRA SPRAY VALVE, NO WALL BRACKET	
		OPTIONS OR MODIFICATIONS: <input type="checkbox"/> SUPPLY LINES (24" OR 36") CIRCLE LENGTH <input type="checkbox"/> ADD-ON FAUCET (6", 8", 10", 12", 14", 16") CIRCLE <input type="checkbox"/> IN-LINE DUAL CHECK VALVE <input type="checkbox"/> BRUSH <input type="checkbox"/> ELBOWS <input type="checkbox"/> VANDAL RESISTANT KIT <input type="checkbox"/> HANDLES (CROSS OR WRIST) CIRCLE STYLE <input checked="" type="checkbox"/> OTHER <u>EZ INSTALL ADAPTERS</u>	
		FEATURES CONTROL VALVE * 8" BACKSPASH MOUNT * INTERNAL SPRING LOADED CHECK VALVES * SWIVELLING SEAT DISKS * HOT SIDE STEM - RIGHT HAND * COLD SIDE STEM - LEFT HAND * STAINLESS STEEL SEATS * STAINLESS STEEL SEAT SCREWS * STAINLESS STEEL HANDLE SCREWS * 1/2" SLIP JOINT KIT HOSE * 36" LENGTH * STAINLESS STEEL END FITTINGS * STAINLESS STEEL EXTERNAL JACKET * 3 PLY FIBER REINFORCED INTERNAL RUBBER HOSE * REPAIRABLE IN FIELD WITH SIMPLE TOOLS ULTRA SPRAY VALVE * LOWEST ENERGY USER - 1.15 GPM @ 60 PSI * CLEANS FASTER - TEST PROVEN * ENGINEERED TO LAST - NO 'O' RINGS TO LEAK * INTERCHANGEABLE - FITS ALL BRANDS SYSTEM LIMITS * TEMP: 40°F MIN. TO 140°F MAX. * PRESSURE: 200 PSI MAX. STATIC SHIPPING WEIGHT * 12.0 LBS	
EPAct 2005 Compliant  ANSI/A112.18.1M		 FISHER MANUFACTURING COMPANY TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com	