APPLICATION:		PRODUCT NAME:
JOB NAME:		SINGLE DECK DUAL CONTROL  SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS
QUANTITY:	ITEM NO.	MODEL:
- Mari		☐ 2110 ULTRA SPRAY VALVE, NO WALL BRACKET☐ 2110-WB ULTRA SPRAY VALVE, WALL BRACKET☐
1/2" NPT FEMALE INLETS	<b>mm</b> ]	OPTIONS OR MODIFICATIONS:  SUPPLY LINES (24" OR 36") CIRCLE LENGTH  ADD-ON FAUCET (6", 8", 10", 12", 14", 16") CIRCLE  IN-LINE DUAL CHECK VALVE  BRUSH  VANDAL RESISTANT KIT  HANDLES (CROSS OR WRIST) CIRCLE STYLE  OTHER  FEATURES  CONTROL VALVE  SINGLE DECK DUAL CONTROL  INTERNAL SPRING LOADED CHECK VALVES  SWIVELLING SEAT DISKS  HOT SIDE STEM - RIGHT HAND  COLD SIDE STEM - LEFT HAND  STAINLESS STEEL SEATS SETAINLESS STEEL SEATS  STAINLESS STEEL SEAT SCREWS  STAINLESS STEEL BRAIDED INLET HOSES  HOSE  36" LENGTH  STAINLESS STEEL END FITTINGS  STAINLESS STEEL END FITTINGS  STAINLESS STEEL END FITTINGS  STAINLESS STEEL END FITTINGS  STAINLESS STEEL END WITH SIMPLE TOOLS  ULTRA SPRAY VALVE  * LOWEST ENERGY USER - 1.15 GPM @ 60 PSI  *CLEANS FASTER - TEST PROVEN  * ENGINEERED TO LAST - NO 'O' RINGS TO LEAK  * INTERCHANGEABLE - FITS ALL BRANDS  WALL BRACKET  * ADJUSTS FROM 2" TO 12"  SYSTEM LIMITS  * TEMP: 40°F MIN. TO 140°F MAX.  * PRESSURE: 200 PSI MAX. STATIC  SHIPPING WEIGHT  * 12.0 LBS
ROUGH-IN:	FOOTPRINT:	
Ø1-1/4" [32mm]	1-3/4" [66mm]	FISHER MANUFACTURING COMPANY
EPAct 2005 Compliant	(f) ANSI/A112.18.1M	TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com