



THE ART OF SOUP



VISIT THE SOUP SERVICE SOLUTIONS SECTION OF VOLLRATH.COM, A COMPREHENSIVE LIBRARY OF PRODUCTS AND RESOURCES DESIGNED SPECIFICALLY FOR YOUR HIGH PROFIT SOUP OFFERING.



NEW

CERTIFICATION(S)



COUNTERTOP INDUCTION SOUP RETHERMALIZERS ARE AVAILABLE

See pages 35-36 in Countertop Warming and Display



Induction Drop-In Soup Warmers & Rethermalizers

NO WATER REQUIRED

- Induction technology means no water, no filling, no re-filling and no scaling
- Ships with insets and covers
- Immediate start-up, no pre-heating
- 3 thermistor temperature sensing ensures highest food quality and 100% food yield
- Includes under-counter mounting brackets
- Highly efficient warmers are 250W, 2.1 AMPS
- Heat is dry and does not require drains
- Set temperatures in 1° increments or presets for soup, cream soup, mac n' cheese or chili

ITEM	DESCRIPTION	OVERALL WIDTH IN (CM)	DROP-IN BODY WIDTH IN (CM)	DROP-IN MAX WIDTH IN (CM)	WELL DEPTH IN (CM)	CUTOUT DIAMETER IN (CM)	VOLTAGE	WATTS	AMPS	PLUG	CASE LOT
74701DW	Drop-in induction warmer, 7 qt	11 $\frac{1}{8}$ (30.2)	10 $\frac{3}{8}$ (26.4)	10 $\frac{1}{8}$ (26.5)	6 $\frac{1}{8}$ (17.6)	10 $\frac{1}{8}$ (27)	120	250	2.1	5-15P	1
74701D	Drop-in induction rethermalizer, 7 qt	11 $\frac{1}{8}$ (30.2)	10 $\frac{3}{8}$ (26.4)	10 $\frac{1}{8}$ (26.5)	6 $\frac{1}{8}$ (17.6)	10 $\frac{1}{8}$ (27)	120	800	6.7	5-15P	1
741101DW	Drop-in induction warmer, 11 qt	13 $\frac{3}{8}$ (35.2)	12 $\frac{3}{8}$ (31.4)	12 $\frac{1}{8}$ (31.6)	6 $\frac{1}{8}$ (17.6)	12 $\frac{1}{8}$ (32.1)	120	250	2.1	5-15P	1
741101D	Drop-in induction rethermalizer, 11 qt	13 $\frac{3}{8}$ (35.2)	12 $\frac{3}{8}$ (31.4)	12 $\frac{1}{8}$ (31.6)	6 $\frac{1}{8}$ (17.6)	12 $\frac{1}{8}$ (32.1)	120	800	6.7	5-15P	1

CERTIFICATION(S)



Mounting brackets standard

Soup Well Modular Drop-Ins

- 6-foot (183 cm) power cord and 4-foot (122 cm) control cord
- Double wall construction
- Deep drawn stainless wells
- High-density glass fiber insulation
- $\frac{3}{4}$ " (1.9 cm) drain with ball valve shut-off
- Well height: 7 $\frac{1}{16}$ " (19.5 cm)
- Auto-fill option available –see below
- NSF4 listed

INFINITE CONTROL ITEM #	THERMOSTATIC CONTROL ITEM #	HOLDS INSET SIZE	DIAMETER OVER FLANGE IN (CM)	DIAMETER CUTOUT IN (CM)	WELL OUTER DIAMETER IN (CM)	WATTS	VOLTAGE	AMPS	PLUG	CASE LOT
36462	3646210	7 $\frac{1}{4}$ qt (6.9 L)	11 $\frac{1}{8}$ (28.4)	10 $\frac{3}{8}$ (26.8)	10 $\frac{1}{8}$ (26.2)	720	120	6	5-15P	1
36464	3646410	11 qt (10.5 L)	12 $\frac{3}{8}$ (32.5)	12 $\frac{1}{4}$ (31.1)	12 (30.5)	720	120	6	5-15P	1
36463	3646310	7 $\frac{1}{4}$ qt (6.9 L)	11 $\frac{1}{8}$ (28.4)	10 $\frac{3}{8}$ (26.8)	10 $\frac{1}{8}$ (26.2)	720-960	208-240	3.5-4	6-15P	1
36465	3646510	11 qt (10.5 L)	12 $\frac{3}{8}$ (32.5)	12 $\frac{1}{4}$ (31.1)	12 (30.5)	720-960	208-240	3.5-4	6-15P	1

Note: Modular Drop-Ins cannot be cancelled or returned.