

# Manual Griddles

## Standard Features

- Stainless steel exterior & interior
- Stainless steel grease drawer
- Heavy duty 3/4" thick polished steel griddle plate
- 30,000 BTU Burners per 12" section with standby pilots
- Independent manual controls for each 12" section
- Stainless steel legs standard
- 3/4" NPT rear gas connection and regulator standard

### MODELS:

ATMG-24 / ATMG- 36 / ATMG-48

**ATMG-24**



**ATMG-36**



**ATMG-48**



1 YR WARRANTY ON ALL PARTS AND LABOR (US ONLY)



Conforms to ANSI  
STD Z83.11b-2009 (2011)  
Certified to CSA  
STD 1.8B-2009 (2011)  
Conforms to NSF/ANSI STD.4



## SPECIFICATIONS

| Models  | Burners and control method              | Gas type | Intake-tube pressure (in. W.C.) | Per BTU B.T.U./h | Total BTU B.T.U./h | Regulator | Work area (inch)                        | Net weight (lbs) | Gross weight (lbs) |
|---------|-----------------------------------------|----------|---------------------------------|------------------|--------------------|-----------|-----------------------------------------|------------------|--------------------|
| ATMG-24 | 2 Burners<br>Independent Manual Control | NG       | 4                               | 30,000           | 60,000             | 4" w.c.   | 23 <sup>9/10</sup> × 19 <sup>9/10</sup> | 160.9            | 194.5              |
|         |                                         | LP       | 10                              | 30,000           | 60,000             | 10" w.c.  |                                         |                  |                    |
| ATMG-36 | 3 Burners<br>Independent Manual Control | NG       | 4                               | 30,000           | 90,000             | 4" w.c.   | 35 <sup>7/10</sup> × 19 <sup>9/10</sup> | 229              | 280.9              |
|         |                                         | LP       | 10                              | 30,000           | 90,000             | 10" w.c.  |                                         |                  |                    |
| ATMG-48 | 4 Burners<br>Independent Manual Control | NG       | 4                               | 30,000           | 120,000            | 4" w.c.   | 47 <sup>9/10</sup> × 19 <sup>9/10</sup> | 294              | 414                |
|         |                                         | LP       | 10                              | 30,000           | 120,000            | 10" w.c.  |                                         |                  |                    |

## PLAN VIEW

