

# Replacement Parts for Silver Series Plumbing



## Silver Series 1/4 Turn Ceramic Valve Repair Kit (10-4, 11-4, 13-8 Series)

- Fits all 10-4, 11-4, and 13-8 series faucets
- Includes (1) hot and (1) cold ceramic valve set with handles
- Fully assembled, easy to install

Model  
**21-300L**



## Silver Series Compression Valve Repair Kit (Old Style 10-4, 11-4, 13-8 Series)

- Fits old style 10-4, 11-4, and 13-8 series faucets
- Includes (1) hot and (1) cold compression valve set with handles
- Fully assembled, easy to install

Model  
**21-325L**



## Silver Series 1/4 Turn Ceramic Valve Repair Kit (12-8 Series)

- Fits all 12-8 series faucets
- Includes (1) hot and (1) cold ceramic valve set with handles
- Fully assembled, easy to install

Model  
**21-310L**



## Silver Series Compression Valve Repair Kit (Old Style 12-8 Series)

- Fits old style 12-8 series
- Includes (1) hot and (1) cold compression valve set with handles
- Fully assembled, easy to install

Model  
**21-355L**



## Silver Series Lever Handle Kit

- Fits all Krowne faucets
- Lever style
- Contains (2) screws, (2) handles, and hot & cold indicator
- Solid chrome plated brass

Model  
**21-305**



## Silver Series Wrist Blade Handle Kit

- Fits all Silver Series faucets
- 4" length
- Contains (2) screws, (2) handles, and hot & cold indicator
- Solid chrome plated brass

Model  
**21-312**



## Silver Series Coupling Flanges

- Fits 12-8 Silver Series 8" center wall mount faucet
- 1/2" NPT female inlet
- Two rubber washers

Model  
**21-400L**



## Replacement Washer Set

- 12 pcs. per set
- Fits Silver Series coupling flanges

Model  
**20-302**

## Swing Spouts

- Fits Krowne Silver Series Faucets



Model	Spout Size	Flow Rate
<b>19-220L</b>	6" Swing Spout	1.8 GPM
<b>19-221L</b>	8" Swing Spout	1.8 GPM
<b>19-222L</b>	10" Swing Spout	1.8 GPM
<b>19-223L</b>	12" Swing Spout	1.8 GPM
<b>19-224L</b>	14" Swing Spout	1.8 GPM
<b>19-225L</b>	16" Swing Spout	1.8 GPM

## Gooseneck & Jointed Spouts

- Fits Krowne Silver Series Faucets



Model	Spout Size	Height	Flow Rate
<b>19-226L</b>	18" Jointed Spout	-	1.8 GPM
<b>19-227L</b>	3-1/2"W Gooseneck	7-1/4"	0.5 GPM
<b>19-228L</b>	6"W Gooseneck	8-1/2"	1.8 GPM
<b>19-229L</b>	8-1/2"W Gooseneck	10"	1.8 GPM