

UFP0350 Flake Ice Machines

Model

LJ UFP0350A



Flake Ice Machine

*Fits under standard counter heights

Standard Equipment

UFP0350

Ice Scoop, 6" Bin Legs, Standard Legs Adjustable from 4-1/2" to 6"

Standard Features

- Up to 398 lbs. (181 kgs) daily flake ice production.
- Up to 60 lbs. (27 kgs) ice storage capacity.
- Flake ice is perfect for food display, salad bars, and cold therapy/healthcare.
- High load maintenance free bearings for enhanced reliability.
- R290 Refrigerant is environmentally friendly with less ozone depletion compared to R404.
- Easy access door, slides up & out of the way.



Ice Machine Electric

*115/60/1. (230/50/1 also available.) 115/60/1 ice machines are factory pre-wired with a 6' (180 cm power cord and NEMA 5-15P plug configuration.

*230/50/1 ice machines are factory pre-wired with a 6' (180 cm) power cord with no pluq.

Total ampacity:

Air-cooled: 7.5 amps.

Maximum fuse size:

Air-cooled: 15 amps.

HACR-type circuit breakers can be used in place of fuses

Specifications

Condenser Heat of Rejection (BTU per Hour):

5.121 (average)

Compressor

Nominal rating: 3/4 HP

Refrigerant

R290A

Operating Limits

Ambient Temperature Range:

50°-110°F (10°-43°C)

Water Temperature Range: 37°-90°F (3°-32°C)

Water Pressure Ice Maker Water In:

Min. 14 psi (96.5 kPA) Max. 80 psi (551.6 kPA)

Ice Shape

- Flake ice is small hard bits of ice ideally suited for presentation applications.
- With 73% ice to water ratio, ice forms around objects without bruising and holds in place without tipping/ spilling.



Ice shown actual size







QUALITY MANAGEMENT SYSTEM
CERTIFIED BY DNV





UFP0350 29.06" 27.17" (73.81 cm) (69.00 cm) $\textcircled{A} \, \mathsf{Electrical} \,$ Entrance ® 3/8" (0.95 cm) N.P.T. Ice Making Water Inlet © 1/2" (1.27 cm) N.P.T. Ice Making Water Outlet 33.52" (85.1 cm) Installation Note Minimum installation cleara Sides: 2" (5 cm) Back: 8" (20 cm) 6.00" (15.24 cm)

Space-Saving Designs



UFP0350


Height 39.52" 100.4 cm
Width 29.06" 73.81 cm
Depth 27.17"

69.00 cm Bin 50 lbs.

Storage 23 kgs
Height includes adjustable bin legs 4.50" to 6.00",

11.43 cm to 15.24 cm) set at 6.00" (15.24 cm).

Air Flow Overhead View



Air-cooled Ice Machine			Ice Production 24 Hours		Power	Potable Water			
	Model	Ice Shape	70°Air/50°F Water 21°Air/10°C Water		kWh/100 lbs @ 90°Air/70°F	Usage	Application Capacity*		2018 AHRI Capacity **
	UFP0350A	Flake	398 lbs.	328 lbs.	5.27	12 gal.	60 lbs.	40 lbs	2.04 Cu ft
			181 kgs	149 kgs		45.4 L	27 kgs	18 kg	0.06 Cu m

"A" following model number indicates "Air" condensing unit. Test conditions are $90^{\circ}F/32^{\circ}C$ air, $70^{\circ}F/21^{\circ}C$ water, and 30 ± 3 psig water inlet pressure.

* Application capacity is based on 90% of the volume x 33 lbs/ft3 average density of ice must be managed

***2018 AHRI certified measurement for bin capacity

Manitowoc Ice reserves the right to make changes to the design or specifications without prior notice.

2110 South 26th Street Manitowoc, WI 54220 Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com

6507C 06/22

^{**2017} Approved AHRI capacity is based on 80% of the total volume x 30 lbs/ft3 average density of ice