

TMT-SERIES
as indicated 

DIGITAL THERMOMETERS

**KEEP
FOOD
SAFE**





**KEEP ON
PACE**



Winco digital thermometers are compliant with FDA standards



DIGITAL

- ◆ Easy-read LCD display and excellent, quick response times for fast temperature readings
- ◆ Step-down probe models ideal for delicate foods to avoid breaking skin

ITEM	NSF	TEMPERATURE RANGE	LCD	PROBE	GUIDELINE ON DIAL	MOUNTING / OTHER FEATURES	UOM	CASE
TMT-DG1		-40° - 302°F; -40° - 150°C	1"	4-3/4"L	Meat Cooking Temperature Guide	• Tapered Tip Probe • Protective Sleeve	Each	12/144
TMT-DG2	N/A	-49° - 392°F; -45° - 200°C	1-3/16"	4-3/4"L	Meat Cooking Temperature Guide	• Step-Down Probe • Easy-Read LCD Swivels 180°	Each	12/72
TMT-DG4		-40° - 450°F; -40° - 230°C	1-1/4"	3-1/8"L	HACCP	• Tapered Tip Probe • Hold Function	Each	3/144
TMT-DG5	N/A	-49° - 392°F; -45° - 200°C	1-3/8" Back-Lit	2-7/8"L	Meat Cooking Temperature Guide	• Min. & Max. Feature • Hold Function • Lanyard	Each	12/72
TMT-DG6	N/A	-58 - 572°F; -50 - 300°C	1-7/8"	6"L		• Step-Down Probe • Flip-Down Stand • Magnet Included	Set	24/96
TMT-DG7		-40° - 572°F; -40° - 300°C	1-1/2"	4"L		• Thermocouple • 1.5mm Step-Down Folding Probe • Hold & Auto-Off Functions • Calibratable	Each	12/72
TMT-WD2		-40° - 450°F; -40° - 232°C	1-3/8"W	2-3/4"L		• 1.5mm Step-Down Folding Probe • Auto-Off Function • Lanyard Included	Each	12/96

WATERPROOF DIGITAL THERMOMETERS

- ◆ Compact thermometers provide fast temperature readings for liquids or solids
- ◆ Protective sleeve included
- ◆ Step-down probe models ideal for delicate skinned foods

ITEM	NSF	TEMPERATURE RANGE	LCD	PROBE	MOUNTING / OTHER FEATURES	UOM	CASE
TMT-WD1		-58° - 392°F; -50° - 200°C	7/8"	2-3/4"L	• Tapered Tip Probe • Hold Function	Each	24/96
TMT-WD3		-40° - 500°F; -40° - 260°C	1"W	5"L	• 1.5mm Step-Down Probe • Min./Max. and Hold Functions • Antimicrobial Sleeve • Calibratable	Each	24/72

INFRARED THERMOMETER

- ◆ Point at surface to get an accurate temperature reading, with no risk of cross-contamination.
- ◆ Distance to spot ratio 12:1

ITEM	NSF	TEMPERATURE RANGE	LCD	PROBE	MOUNTING / OTHER FEATURES	UOM	CASE
TMT-IF1	N/A	-26° - 608°F; -32° - 320°C	1" Back-Lit	N/A	• Auto Temp. Hold • Auto Off When Idle 20 Seconds • Laser ON/OFF	Each	12/48